

Commercial Grade

Dispensable Epoxy Absorber

**MATERIAL**


Epoxy resin

**FEATURES**



- Reduces RF signals, suppresses standing waves and RF noise
- Adheres to metal surfaces
- Can be machined after curing
- Electrically equivalent to cavity resonance sheet absorber products
- Low outgassing
- RoHS compliant and halogen free

PROPERTIES	CR-DE-2
Color	Dark Grey
Density	3.11 g/cm ³
Softness	65 Shore A
Operating Temperature	-55 to 125 °C

PROPERTIES	CR-DE-2
Flammability Rating	UL 94 HB
Minimum Thickness	0.5 mm
Outgassing	Low

Permittivity and Permeability**Attenuation**

Based on the test result of permittivity and permeability

**Cavity Resonance**

GET IN TOUCH

EMAIL: SUPPORT@TENNMAX.COM

TEL: +1 360-567-0707

This information and our technical advice – whether verbal, in writing or by way of trials – are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery. V5



TENNMAX.COM